



КЛЕММНЫЕ БЛОКИ &gt; ПРОЧИЕ ПРОДУКТЫ &gt; КЛЕММНЫЕ БЛОКИ

## PSK 1/12 Бежевый

Артикул (SKU): 420120

Винтовая клеммная колодка 2,5 мм<sup>2</sup>, 22-полюсная

### Коммерческая информация

Код продажи продукта	<b>420120</b>
Единица Упаковки	<b>75 шт.</b>
Номер таможенного тарифа	<b>853690950000</b>
Вес за единицу, включая упаковку	<b>0.04 kg.</b>

### Техническая информация

#### PRODUCT FEATURES

Number of Connections	<b>24</b>
Color	<b>Beige</b>
Number of Levels	<b>12</b>
Insulation Material	<b>PA</b>
UL 94 Flammability Class	<b>V2</b>
Impulse Voltage Category	<b>III</b>
Insulation Material Group	<b>I</b>
Pollution Degree	<b>3</b>
Connection According to Standard	<b>IEC 60998-2-1</b>
Continuous Operating Temperature max.	<b>120 °C</b>
Continuous Operating Temperature min.	<b>-55 °C</b>

#### ELECTRICAL FEATURES

Nominal Impulse Voltage	<b>3 Kv</b>
-------------------------	-------------

Nominal Current	<b>24 A</b>
Nominal Voltage	<b>400 V</b>

## CONNECTION DATA

Connection Type	<b>Screw Connection</b>
Single-core min. conductor cross-section	<b>0,2 mm<sup>2</sup></b>
Single-core max. conductor cross-section	<b>4 mm<sup>2</sup></b>
Conductor Cross Section Awgkcmil Min	<b>24 AWG</b>
Conductor Cross Section Awgkcmil Max	<b>12 AWG</b>
Multi-core min. conductor cross-section	<b>0,2 mm<sup>2</sup></b>
Multi-core max. conductor cross-section	<b>4 mm<sup>2</sup></b>
Multi-core min. conductor cross-section with ferrule	<b>0,25 mm<sup>2</sup></b>
Multi-core max. conductor cross-section with ferrule	<b>2,5 mm<sup>2</sup></b>
Min. Stripping Length	<b>5 mm</b>
Max. Stripping Length	<b>6 mm</b>
Internal cylindrical indicator	<b>A3</b>
Tightening Torque Min	<b>0,4 Nm</b>
Tightening Torque Max	<b>0,6 Nm</b>

## DIMENSIONS

Width	<b>15 mm</b>
Length	<b>109 mm</b>
Height	<b>16,25 mm</b>