



КЛЕММНЫЕ БЛОКИ > ПРУЖИННЫЕ КЛЕММНЫЕ БЛОКИ >
ПРЕДОХРАНИТЕЛЬНЫЕ КЛЕММЫ

SRD 4FSLD 48V AC/DC Серый

Артикул (SKU): 312279

4 мм² клемма с двухслойным предохранителем (LED 24VAC/DC)
(5×20)

Коммерческая информация

| | |
|----------------------------------|---------------------|
| Код продажи продукта | 312279 |
| Единица Упаковки | 28 шт. |
| Номер таможенного тарифа | 853630100000 |
| Вес за единицу, включая упаковку | 0.03 kg. |

Техническая информация

| PRODUCT FEATURES | |
|--|--------------------------------------|
| Number of Connections | 4 |
| Color | Grey |
| Number of Levels | 2 |
| Insulation Material | PA |
| UL 94 Flammability Class | V0 |
| Impulse Voltage Category | III |
| Insulation Material Group | I |
| Pollution Degree | 3 |
| Connection According to Standard | IEC 60947-7-1 / IEC 60947-7-3 |
| Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26 | HL 1-HL 2-HL 3 |
| Continuous Operating Temperature max. | 130 °C |
| Continuous Operating Temperature min. | -60 °C |

| | |
|-----------|---------------|
| Fuse | G/5x20 |
| Fuse Type | Glass |

ELECTRICAL FEATURES

| | |
|---------------------------|--------------|
| Nominal Impulse Voltage | 6 Kv |
| Nominal Current | 32 A |
| Nominal Voltage | 500 V |
| Maximum Load Current | 41 A |
| Nominal Current In Fuse | 10 A |
| Maximum Load Current Fuse | 10 A |
| Nominal Voltage Fuse | 48 V |

CONNECTION DATA

| | |
|--|----------------------------|
| Connection Type | Spring Connection |
| Single-core min. conductor cross-section | 0,08 mm² |
| Single-core max. conductor cross-section | 6 mm² |
| Conductor Cross Section Awgkcmil Min | 28 AWG |
| Conductor Cross Section Awgkcmil Max | 10 AWG |
| Multi-core min. conductor cross-section | 0,14 mm² |
| Multi-core max. conductor cross-section | 4 mm² |
| Multi-core min. conductor cross-section with ferrule | 0,14 mm² |
| Multi-core max. conductor cross-section with ferrule | 4 mm² |
| Min. Stripping Length | 8 mm |
| Max. Stripping Length | 10 mm |
| Internal cylindrical indicator | A4 |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve | 1 mm² |

DIMENSIONS

| | |
|-----------------|-----------------|
| Width | 6,2 mm |
| Length | 116,6 mm |
| Height Mr 35X75 | 77,8 mm |

Height MR 35x15

85,3 mm
