



КЛЕММНЫЕ БЛОКИ > ПРУЖИННЫЕ КЛЕММНЫЕ БЛОКИ > ЗАЗЕМЛЯЮЩИЕ КЛЕММЫ

## SRD 6T Жёлто-зелёный

Артикул (SKU): 337210

Клемма Cage Clamp 6 мм<sup>2</sup>, заземляющая

### Коммерческая информация

Код продажи продукта	<b>337210</b>
Единица Упаковки	<b>60 шт.</b>
Номер таможенного тарифа	<b>853690950000</b>
Вес за единицу, включая упаковку	<b>0.02433 kg.</b>

### Техническая информация

PRODUCT FEATURES	
Number of Connections	<b>2</b>
Color	<b>Yellow/Green</b>
Number of Levels	<b>1</b>
Insulation Material	<b>PA</b>
UL 94 Flammability Class	<b>V0</b>
Impulse Voltage Category	<b>III</b>
Insulation Material Group	<b>I</b>
Pollution Degree	<b>3</b>
Protective Conductor Type	<b>PE</b>
Connection According to Standard	<b>IEC 60947-7-2</b>
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	<b>HL 1 - HL 2 - HL 3</b>
Continuous Operating Temperature max.	<b>130 °C</b>
Continuous Operating Temperature min.	<b>-60 °C</b>

## ELECTRICAL FEATURES

Nominal Impulse Voltage	<b>8 Kv</b>
-------------------------	-------------

## CONNECTION DATA

Connection Type	<b>Spring Connection</b>
-----------------	--------------------------

Single-core min. conductor cross-section	<b>0,2 mm<sup>2</sup></b>
--	---------------------------

Single-core max. conductor cross-section	<b>10 mm<sup>2</sup></b>
--	--------------------------

Conductor Cross Section Awgkcmil Min	<b>24 AWG</b>
--------------------------------------	---------------

Conductor Cross Section Awgkcmil Max	<b>8 AWG</b>
--------------------------------------	--------------

Multi-core min. conductor cross-section	<b>0,2 mm<sup>2</sup></b>
---	---------------------------

Multi-core max. conductor cross-section	<b>6 mm<sup>2</sup></b>
---	-------------------------

Multi-core min. conductor cross-section with ferrule	<b>0,25 mm<sup>2</sup></b>
--	----------------------------

Multi-core max. conductor cross-section with ferrule	<b>6 mm<sup>2</sup></b>
--	-------------------------

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	<b>1,5 mm<sup>2</sup></b>
--	---------------------------

Min. Stripping Length	<b>10 mm</b>
-----------------------	--------------

Max. Stripping Length	<b>12 mm</b>
-----------------------	--------------

Internal cylindrical indicator	<b>A5</b>
--------------------------------	-----------

## DIMENSIONS

Width	<b>8,00 mm</b>
-------	----------------

Length	<b>72,50 mm</b>
--------	-----------------

Height Mr 35X75	<b>44,10 mm</b>
-----------------	-----------------

Height MR 35x15	<b>51,60 mm</b>
-----------------	-----------------