

КЛЕММНЫЕ БЛОКИ > АКСЕССУАРЫ > ТЕСТОВЫЕ РОЗЕТКИ

TST 1,5 Серый

Артикул (SKU): 499659

Клемма Cage Clamp 1,5 мм², тестовая

Коммерческая информация

Код продажи продукта	499659
Единица Упаковки	50 шт.

Техническая информация

PRODUCT FEATURES	
Number of Connections	1
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	HL 1 - HL 2 - HL 3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C

ELECTRICAL FEATURES	
Nominal Impulse Voltage	8 Kv
Nominal Voltage	500 V
Nominal Current In Fuse	10 A

CONNECTION DATA

Connection Type	Spring Connection
Single-core min. conductor cross-section	0,08 mm²
Single-core max. conductor cross-section	1,5 mm²
Conductor Cross Section Awgkcmil Min	28 AWG
Conductor Cross Section Awgkcmil Max	16 AWG
Multi-core min. conductor cross-section	0,08 mm²
Multi-core max. conductor cross-section	1,5 mm²
Multi-core min. conductor cross-section with ferrule	0,08 mm²
Multi-core max. conductor cross-section with ferrule	1,5 mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	0,5 mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	0,5 mm²
Min. Stripping Length	8 mm
Max. Stripping Length	10 mm
Internal cylindrical indicator	A1

DIMENSIONS

Width	4,20 mm
Length	17,67 mm
Height	52,07 mm